



SECTION 1: DESCRIPTION & BENEFITS

- PE-fabric backing with high tensile strength
- Coated with aggressive rubber adhesive
- Grey, white, brown, silver, yellow, red color are available
- Extremely easy for hand-tear, easy-used by workers
- Tear cleanly without loose thread hanging off the end
- Excellent resistance to moisture and vapor
- Combination of baking material ensures high flexibility and conformability

SECTION 2: SPECIFICATIONS

Product Characteristics	Performance Data	Test Method
Total Thickness	160 microns (6.4 mil)	PSTC-133/ASTM D3652
Cloth Weaves	35 mesh	PSTC-133/ASTM D3652
Color	Grey, white, red, etc.	Visual Inspection
Peel Adhesion	13 N/25mm (46.8 Oz/In)	PSTC-101/ASTM D3330
Static Shear	≥24 Hours	PSTC-107/ASTM D3654
Tensile Strength	85 N/25mm (19.3 Lb/In)	PSTC-131/ASTM D3759
Elongation at Break	10.0%	PSTC-131/ASTM D3759
Service Temp.	-20 ~ +80°C (-4 ~ +176 °F)	
Operating Temp.	+10 ~ +40°C(+50 ~ +105 °F)	

SECTION 3: APPLICATIONS & OTHER DETAILS

- Floor sealing, carton sealing
- Duct wrapping & sealing, splicing
- Carpet repairing
- Seaming, patching, bundling
- Other general purpose for building industry



Sliced roll width available (or customized): 48,50,72,75,96,100 mm, etc

Log roll: 1000/1200 mm x 45m or 50m

Jumbo roll: 1000/1200 mm x 1000m, 2000m, 3000m, etc`

Tolerance: Thickness: +/- 10% Width: +/-1.0mm Length: +/- 0.4m

Storage: Indoor storage: -5°C-40°C(humidity:< 80%), cool & dry, free of direct sunlight

Shelf Life: 12 months in room temp.

N.B. Please keep the operating surface clean, dry, and free of grease or other dirt & dust. So that **Egret Tape** can have a best performance.

Changzhou Egret Manufacturing Co., Ltd

No.4, Tongshun Rd, Henglin Town, Changzhou 213101 • China

T: +86 519 8878 9969 Ext. 807 Email: info@egretmfg.com Website: www.egretmfg.com